

**2015**  
**Virginia Department of Transportation**  
**Daily Traffic Volume Estimates**  
**Including Vehicle Classification Estimates**

where available

**Special Locality Report**

**136**

City of Waynesboro

Information in this report is included in Report

**07**

(Augusta County)

Prepared By  
**Virginia Department of Transportation**  
**Traffic Engineering Division**

In Cooperation With  
**U.S. Department of Transportation**  
**Federal Highway Administration**

Virginia Department of Transportation  
Traffic Engineering Division  
Traffic Monitoring Section

The Virginia Department of Transportation (VDOT) conducts a program where traffic count data are gathered from sensors in or along streets and highways and other sources. From these data, estimates of the average number of vehicles that traveled each segment of road are calculated. VDOT periodically publishes booklets listing these estimates.

One of these booklets, titled "Average Daily Traffic Volumes with Vehicle Classification Data, on Interstate, Arterial and Primary Routes" includes a list of each Interstate and Primary highway segment with the estimated Annual Average Daily Traffic (AADT) for that segment. AADT is the total annual traffic estimate divided by the number of days in the year. This booklet also includes information such as estimates of the percentage of the AADT made up by 6 different vehicle types, ranging from cars to double trailer trucks; estimated Annual Average Weekday Traffic (AAWDT), which is the number of vehicles estimated to have traveled the segment of highway during a 24 hour weekday averaged over the year; as well as Peak Hour and Peak Direction factors used by planners to formulate design criteria.

In addition to the Primary and Interstate publication, one hundred books are published periodically, one for each of 100 areas across the state defined by VDOT for record-keeping purposes. These books include traffic volume estimates for roads within the county, cities, and towns within the area. These books are titled "Daily Traffic Volumes Including Vehicle Classification Estimates, where available; Jurisdiction Report numbers 00 through 99".

Also available are a number of reports summarizing the average Vehicle Miles Traveled (VMT) in selected jurisdictions and other categories of highways. There are many different ways to present traffic volume summary information. Because the user determines the value of each presentation, the reports have been redesigned based on user requests and feedback. The people of the VDOT Traffic Engineering Division Traffic Monitoring Section who produce these books welcome requests for other helpful ways of presenting the summary information.

A compact disc (CD) is available that includes files in the Adobe® Portable Document Format (PDF) that can be displayed, searched, and printed using common desktop computer equipment. The CD includes the publications described above as well as a number of other reports, including specialized VMT summaries and smaller AADT reports for each city and town separately.

## Publication Notes

### Parallel Roads

For road inventory and management purposes, some roadways are counted separately by direction and have separately published traffic estimates for each direction of travel. Examples of such roadways are the interstate system and routes with separated facilities and (usually) one-way traffic facilities in urban areas. In these publications, they are referred to as parallel roads. As a convenience for the users of the publication, the listing for segments of roads with parallel segments are published with both the traffic estimates for their own direction of travel (e.g. I-95 Northbound) as well as the estimate of the total of all traffic on the same route including parallel roadways (all directions of I-95). The publication will have a "Combined Traffic Estimates for Parallel Roadways on this Route" or "Combined Traffic" identifiers for the combined direction of travel estimates.

Roadways such as I-395 with a North segment, a South segment and a separate Reversible lane segment will have the estimate for more than two parallel roadways included in the entire combined traffic estimate.

Some routes have very complicated paths through cities and towns. These parallel paths may be too complex to allow a relationship between nearby sections of the opposite direction on the same route. In this case, to indicate that the traffic estimates for such a road segment may not include all directions of traffic on that route, the line that would list the combined values will indicate "NA" for not available.

---

VDOT's traffic monitoring program includes more than 100,000 segments of roads and highways ranging from several mile sections of Interstate highways to very short sections of city streets. Due to problems experienced obtaining some traffic count data, and the level of quality necessary to maintain confidence in the data, no estimate is currently available for some segments of roadway. These segments are included in the publications indicating "NA" for not available. It is the intention of the VDOT Traffic Engineering Division Traffic Monitoring group to obtain the data necessary and to report traffic volume estimates on all road segments included in these publications.

Many of the road segments in this program are local secondary roads. The amount and detail of data collected on these roads are not as great as the data collected on higher volume roads. The vehicle classification, average weekday traffic volumes, and the theoretical design hour traffic volumes are not calculated for these roads. The publications indicate "NA" for the information that is not available.

This publication is based on a traffic monitoring program initiated in 1997. Because the data collection techniques and statistical evaluation processes are different than those used in previous years, comparison with previous publications may be misleading.

Glossary of Terms:

**Route:** The Route Number assigned to this segment of roadway with the master inventory route number if this is an overlapping route, with official street or highway name if available.

**Length:** Length of the traffic segment in miles.

**AADT:** Annual Average Daily Traffic. The estimate of typical daily traffic on a road segment for all days of the week, Sunday through Saturday, over the period of one year.

**QA: Quality of AADT:**

- A Average of Complete Continuous Count Data
- B Average of Selected Continuous Count Data
- F Factored Short Term Traffic Count Data
- G Factored Short Term Traffic Count Data with Growth Element
- H Historical Estimate
- M Manual Uncounted Estimate
- N AADT of Similar Neighboring Traffic Link
- O Provided By External Source
- R Raw Traffic Count, Unfactored

**4Tire:** Percentage of the traffic volume made up of motorcycles, passenger cars, vans and pickup trucks.

**Bus:** Percentage of the traffic volume made up of busses.

**2Axle Truck:** Percentage of the traffic volume made up of 2 axle single unit trucks (not including pickups and vans).

**3+Axle Truck:** Percentage of the traffic volume made up of single unit trucks with three or more axles.

**1Trail Truck:** Percentage of the traffic volume made up of units with a single trailer.

**2Trail Truck:** Percentage of the traffic volume made up of units with more than one trailer.

**QC: Quality of Classification Data:**

- A Average of Complete Continuous Count Data
- B Average of Selected Continuous Count Data
- C Short Term Classified Traffic Count Data
- F Factored Short Term Traffic Count Data
- H Historical Estimate
- M Mass Collective Average
- N Classification Estimates of Similar Neighboring Traffic Link

**K Factor:** The estimate of the portion of the traffic volume traveling during the peak hour or design hour.

**QK:** Quality of the K Factor estimate:

- A Factor based on 30th Highest Hour Observed During at least 250 days of Continuous Traffic Data
- B Factor based on other Hour Observed During Less than 250 days of Continuous Traffic Data
- F Factor based on Highest Hour Collected at in a 48 Hour Weekday Period
- M Factor based on Manual Estimate of design hour
- N Design Hour Factor (K Factor) of Similar Neighboring Traffic Link
- O Provided by External Source

**Dir Factor:** The estimate of the portion of the traffic volume traveling in the peak direction during the peak hour..

**AAWDT:** Average Annual Weekday Traffic. The estimate of typical traffic over the period of one year for the days between Monday through Thursday inclusive.

**QW:** Quality of AAWDT:

- A Average of Complete Continuous Count Data
- B Average of Selected Continuous Count Data
- F Factored Short Term Traffic Count Data
- G Factored Short Term Traffic Count Data with Growth Element
- M Manual Uncounted Estimate
- N AAWDT of Similar Neighboring Traffic Link
- O Provided by External Source

**Year:** Year for which the published values are appropriate. If the Quality of AADT (QA) is "R", the year is the year that the raw traffic count was collected, and if available,

# Route Shield Legend

## Route Systems

- North  
 Interstate Route Traffic volume data for Interstate Routes and some other routes are reported separately by direction, as well as combined.
-  US Route
-  Virginia State Route
-  Frontage Road (F precedes frontage route number)
-  Secondary Route

## Special Routes

- Bus  
 Bus - Business Route  
Bypas - Bypass Route  
Truck - Truck Route
- ALT  
 ALT - Alternate Route  
Wve - Wve Route connector
-  P - Parallel Route; Southbound or Westbound direction lanes of a numbered route where they are on a different road facility than the other direction.
-  The VDOT Maintenance Jurisdiction number is displayed below the Secondary Route Number if the Maintenance Jurisdiction is different than the jurisdiction in the title of the report.

Virginia Department of Transportation  
Traffic Engineering Division  
2015  
Annual Average Daily Traffic Volume Estimates By Section of Route  
City of Waynesboro

Route	Jurisdiction	Length	AADT	QA	4Tire	Bus	-----Truck-----				QC	K Factor	QK	Dir Factor	AAWDT	QW
							2Axle	3+Axle	1Trail	2Trail						
East 64	From: WCL Waynesboro															
	City of Waynesboro (Maint: 07)	0.23	19000	G	89%	1%	1%	1%	9%	0%	F	0.084		19000	G	
Combined Traffic Estimates for 2 Parallel Roadways on this Route:			39000	G	89%	1%	1%	1%	9%	0%	F	0.087	F	0.523	38000	G
East 64	From: US 340 Stuarts Draft Hwy															
	City of Waynesboro (Maint: 07)	1.95	20000	A	89%	1%	1%	1%	9%	0%	C	0.103		19000	A	
Combined Traffic Estimates for 2 Parallel Roadways on this Route:			40000	A	89%	1%	1%	1%	9%	0%	C	0.108	A	0.592	39000	A
East 64	From: Delphine Ave, To 07-624															
	City of Waynesboro (Maint: 07)	0.70	18000	A	89%	1%	1%	1%	9%	0%	F	0.107		17000	A	
Combined Traffic Estimates for 2 Parallel Roadways on this Route:			36000	A	89%	1%	1%	1%	9%	0%	F	0.107	A	0.557	35000	A
East 64 Ramp	From: I-64 East															
	City of Waynesboro (Maint: 07)	0.22	3300	G								0.097		3300	G	
Combined Traffic Estimates for 2 Parallel Roadways on this Route:																
West 64	From: WCL Waynesboro															
	City of Waynesboro (Maint: 07)	0.43	20000	G	89%	1%	1%	1%	9%	0%	F	0.09		19000	G	
Combined Traffic Estimates for 2 Parallel Roadways on this Route:			39000	G	89%	1%	1%	1%	9%	0%	F	0.087	F	0.523	38000	G
West 64	From: US 340 Stuarts Draft Hwy															
	City of Waynesboro (Maint: 07)	2.15	20000	A	89%	1%	1%	1%	9%	0%	C	0.117		20000	A	
Combined Traffic Estimates for 2 Parallel Roadways on this Route:			40000	A	89%	1%	1%	1%	9%	0%	C	0.108	A	0.592	39000	A
West 64	From: Delphine Ave, To 07-624															
	City of Waynesboro (Maint: 07)	0.30	18000	A	89%	1%	1%	1%	9%	0%	F	0.119		18000	A	
Combined Traffic Estimates for 2 Parallel Roadways on this Route:			36000	A	89%	1%	1%	1%	9%	0%	F	0.107	A	0.557	35000	A
West 64 Ramp	From: I-64 West															
	City of Waynesboro (Maint: 07)	0.24	1500	G								0.162		1500	G	
Combined Traffic Estimates for 2 Parallel Roadways on this Route:																
250 Main St	From: WCL Waynesboro															
	City of Waynesboro	0.84	18000	G	99%	0%	0%	0%	0%	0%	F	0.087		0.527	20000	G
250 Main St	From: Carman Ave															
	City of Waynesboro	0.30	18000	G	99%	0%	0%	0%	0%	0%	F	0.085		0.525	20000	G
250 Main St	From: Hopeman Pkwy															
	City of Waynesboro	0.67	12000	G	99%	0%	0%	0%	0%	0%	F	0.088		0.505	13000	G
250 Broad St	From: US 340 Rosser Ave															
	City of Waynesboro	0.25	13000	G	99%	0%	0%	0%	0%	0%	F	0.090		0.864	14000	G
250 Broad St	From: Poplar Ave															
	City of Waynesboro	0.50	11000	G	99%	0%	0%	0%	0%	0%	F	0.092		0.554	12000	G
Combined Traffic Estimates for 2 Parallel Roadways on this Route:																

Virginia Department of Transportation  
Traffic Engineering Division  
2015  
Annual Average Daily Traffic Volume Estimates By Section of Route  
City of Waynesboro

Route	Jurisdiction	Length	AADT	QA	4Tire	Bus	-----Truck-----				QC	K Factor	QK	Dir Factor	AAWDT	QW
							2Axle	3+Axle	1Trail	2Trail						
	From: Wayne Ave															
250 Broad St	City of Waynesboro	0.12	11000	G	99%	0%	0%	0%	0%	F	0.09		0.5	12000	G	
	To: Arch Ave															
	From: Arch Ave															
250 Broad St	City of Waynesboro	0.44	8800	G	98%	0%	1%	0%	1%	C	0.09		0.511	9300	G	
	To: US 340 Main St															
	From: US 340 Main St															
250 340 Main St	City of Waynesboro	0.19	12000	G	97%	0%	1%	0%	1%	C	0.095		0.573	12000	G	
	To: US 340 Broad St															
	From: US 340 Broad St															
250 Main St	City of Waynesboro	1.00	7300	G	97%	0%	1%	0%	1%	C	0.095		0.639	7800	G	
	To: US 340 Delphine Ave															
	From: US 340 Delphine Ave															
250 Main St	City of Waynesboro	0.44	7000	G	97%	0%	1%	0%	1%	C	0.097		0.634	7600	G	
	To: Hunter St															
	From: Hunter St															
	To: ECL Waynesboro															
	From: ECL Waynesboro															
254 Ivy St	City of Waynesboro	1.19	5900	G	97%	0%	1%	1%	1%	C	0.103		0.511	6300	G	
	To: WCL Waynesboro															
	From: WCL Waynesboro															
254 Ivy St	City of Waynesboro	0.52	5500	G	98%	0%	1%	0%	0%	C	0.103		0.637	5900	G	
	To: Hopeman Pkwy															
	From: Hopeman Pkwy															
254 Poplar Ave	City of Waynesboro	0.30	10000	G	98%	0%	1%	0%	0%	C	0.094		0.543	11000	G	
	To: King Ave															
	From: King Ave															
254 Poplar Ave	City of Waynesboro	0.07	3200	G	98%	0%	1%	0%	0%	F	0.117		0.606	3400	G	
	To: Broad St															
	From: Broad St															
	To: Main St															
	From: Main St															
340 Rosser Ave	City of Waynesboro	0.34	27000	G	97%	0%	0%	0%	2%	F	0.093		0.510	28000	G	
	To: WCL Waynesboro															
	From: WCL Waynesboro															
340 Rosser Ave	City of Waynesboro	0.56	29000	G	99%	0%	1%	0%	0%	F	0.091		0.558	31000	G	
	To: I-64															
	From: I-64															
340 Rosser Ave	City of Waynesboro	0.71	18000	G	99%	0%	1%	0%	0%	C	0.089		0.532	19000	G	
	To: Lew Dewitt Blvd															
	From: Lew Dewitt Blvd															
340 Rosser Ave	City of Waynesboro	0.61	13000	G	99%	0%	1%	0%	0%	F	0.083		0.503	13000	G	
	To: Northgate Ave															
	From: Northgate Ave															
340 Rosser Ave	City of Waynesboro	0.56	12000	G	99%	0%	1%	0%	0%	F	0.085		0.521	13000	G	
	To: Forrest Dr															
	From: Forrest Dr															
340 Main St	City of Waynesboro	0.38	8200	G	99%	0%	1%	0%	0%	F	0.090		0.518	8700	G	
	To: US 250 Main St															
	From: US 250 Main St															
	To: Rosser Ave															
	From: Rosser Ave															
340 Main St	City of Waynesboro	0.35	6000	G	99%	0%	1%	0%	0%	F	0.091		0.540	6500	G	
	To: New Hope Rd															
	From: New Hope Rd															
340 Main St	City of Waynesboro	0.14	4700	G	99%	0%	1%	0%	0%	F	0.096		0.518	5100	G	
	To: Wayne Ave															
	From: Wayne Ave															
	To: Arch Ave															



Virginia Department of Transportation  
 Traffic Engineering Division  
 2015  
 Annual Average Daily Traffic Volume Estimates By Section of Route  
 City of Waynesboro

Route	Jurisdiction	Length	AADT	QA	4Tire	Bus	-----Truck-----				QC	K Factor	QK	Dir Factor	AAWDT	QW
							2Axle	3+Axle	1Trail	2Trail						
	From: Arch Ave															
340 Main St	City of Waynesboro	0.39	6400	G	99%	0%	1%	0%	0%	0%	F	0.090	0.565	6800	G	
	To: US 250 Broad St															
	From: US 250 Broad St															
340 250 Main St	City of Waynesboro	0.19	12000	G	97%	0%	1%	0%	1%	0%	C	0.095	0.573	12000	G	
	To: Main St															
	From: Main St															
340 Delphine Ave	City of Waynesboro	0.25	11000	G	97%	0%	1%	1%	1%	0%	F	0.095	0.575	11000	G	
	To: 7th St															
	From: 7th St															
340 Delphine Ave	City of Waynesboro	0.60	10000	G	97%	0%	1%	1%	1%	0%	F	0.092	0.588	11000	G	
	To: Second St															
	From: Second St															
340 Delphine Ave	City of Waynesboro	0.81	8100	G	97%	0%	1%	1%	1%	0%	F	0.094	0.578	8600	G	
	To: Hopeman Pkwy															
	From: Hopeman Pkwy															
340 Delphine Ave	City of Waynesboro	0.25	10000	G	97%	0%	1%	1%	1%	0%	C	0.097	0.651	11000	G	
	To: NCL Waynesboro															
	From: NCL Waynesboro															

Virginia Department of Transportation  
Traffic Engineering Division  
2015  
Annual Average Daily Traffic Volume Estimates By Section of Route  
City of Waynesboro

Route	Length	AADT	QA	4Tire	Bus	-----Truck-----				QC	K Factor	QK	Dir Factor	AAWDT	QW	Year
						2Axle	3+Axle	1Trail	2Trail							
<b>City of Waynesboro</b>																
(F209) Shenandoah Village Dr	0.27	3000	R			US 340 Rosser Ave					NA			NA		06/25/2013
						Dead End										
(F210) Windigrove Dr	0.04	NA				US 340 Rosser Ave					NA			NA		
						End State Maintenance										
(F211) Chinquapin Dr	0.40	610	R			SCL Waynesboro					NA			NA		06/25/2013
						07-1040 Chinquapin Dr; ECL Waynesboro										
(1) Kirby St	0.12	380	G	94%	3%	2%	0%	0%	0%	F	0.137		0.629	400	G	2015
						Shenandoah Ave										
						A Street										
(2) A St	0.22	1400	G	97%	1%	1%	1%	0%	0%	C	0.115		0.633	1500	G	2015
						Kirby Ave										
						ECL Waynesboro										
(5100) Thirteenth St	0.63	4300	G	99%	0%	1%	0%	0%	0%	F	0.103		0.553	4600	G	2015
						Rosser Ave										
						Pine Ave										
(5100) Thirteenth St	0.43	2400	G	99%	0%	1%	0%	0%	0%	C	0.106		0.613	2600	G	2015
						Arch Ave										
(5101) Davis Rd	0.09	3100	G	99%	0%	0%	0%	0%	0%	F	0.097		0.517	3300	G	2015
						Northgate Ave										
						Vedette St										
(5101) Vedette Ave	0.68	3100	G	99%	0%	0%	0%	0%	0%	C	0.098		0.517	3300	G	2015
						Davis Rd										
						Main St										
(5103) Northgate Ave	0.33	3200	G	98%	0%	1%	1%	0%	0%	C	0.096		0.577	3400	G	2015
						US 340 Rosser Ave										
						Meadowbrook Rd										
(5103) Meadowbrook Rd	0.76	3400	G	99%	0%	0%	0%	0%	0%	C	0.093		0.52	3600	G	2015
						Northgate Ave										
						Lyndhurst Rd										
(5104) Hopeman Pkwy	0.89	10000	G	97%	0%	1%	0%	1%	0%	F	0.091		0.523	11000	G	2015
						Main St										
						Ivy St										
(5104) Hopeman Pkwy	0.96	8600	G	97%	0%	1%	0%	1%	0%	F	0.093		0.535	9200	G	2015
						Hopeman Pkwy										
						King Ave										
(5104) Hopeman Pkwy	0.58	7200	G	97%	0%	1%	0%	1%	0%	F	0.096		0.531	7600	G	2015
						Hopeman Pkwy										
						Genicom Dr										
(5104) Hopeman Pkwy	0.29	6500	G	97%	0%	1%	0%	1%	0%	C	0.097		0.618	6900	G	2015
						Hopeman Pkwy										
						Delphine Ave										
(5105) Lyndhurst Rd	1.61	2900	G	98%	1%	1%	0%	0%	0%	C	0.114		0.608	3100	G	2015
						SWCL Waynesboro										
						Meadowbrook Rd										
(5105) Lyndhurst Rd	0.65	5500	G	98%	1%	1%	0%	0%	0%	F	0.104		0.596	5900	G	2015
						Lyndhurst Rd										
						Woodrow Ave										
(5105) Wayne Ave	0.37	5100	G	98%	1%	1%	0%	0%	0%	F	0.093		0.575	5400	G	2015
						Wayne Ave										
						13th St										
(5105) Wayne Ave	0.39	4500	G	98%	1%	1%	0%	0%	0%	F	0.098		0.577	4800	G	2015
						Wayne Ave										
						US 340 Main St										
(5105) Wayne Ave	0.08	4500	N	98%	1%	1%	0%	0%	0%	N	0.098		0.577	4800	N	2015
						Wayne Ave										
						US 250 Broad St										
						Ohio St										
(5105) Florence Ave	0.83	1300	G	98%	1%	1%	0%	0%	0%	F	0.103		0.541	1400	G	2015
						Florence Ave										
						Bridge Ave										

Virginia Department of Transportation  
Traffic Engineering Division  
2015  
Annual Average Daily Traffic Volume Estimates By Section of Route  
City of Waynesboro

Route	Length	AADT	QA	4Tire	Bus	-----Truck-----				QC	K Factor	QK	Dir Factor	AAWDT	QW	Year
						2Axle	3+Axle	1Trail	2Trail							
<b>City of Waynesboro</b>																
5106 New Hope Rd	0.59	580	G	99%	1%	From Poplar Ave				F	0.212		0.830	620	G	2015
						To Hopeman Pkwy										
5106 Whitebridge Rd	0.98	960	G	99%	1%	From Guilford Lane				C	0.115		0.52	1000	G	2015
						To NCL Waynesboro										
5107 King Ave	0.62	4200	G	98%	1%	From Ivy St				F	0.094		0.564	4500	G	2015
						To Bridge St										
5107 King Ave	0.57	3500	G	98%	1%	From Bridge St				C	0.104		0.506	3800	G	2015
						To Hopeman Pkwy										
5108 Poplar Ave	0.29	2000	G	98%	1%	From 13th St				F	0.138		0.517	2100	G	2015
						To Main St										
5109 Windsor Rd	0.43	4000	G	99%	0%	From Delphine Ave				C	0.105		0.601	4200	G	2015
						To Lyndhurst Rd										
5110 4th St	0.31	970	G	98%	0%	From Charlotte Ave				F	0.104		0.526	1000	G	2015
						To Delphine Ave										
5110 4th St	0.46	2300	G	98%	0%	From Delphine Ave				C	0.101		0.598	2400	G	2015
						To Jackson Ave										
5111 Arch Ave	0.77	2900	G	97%	0%	From Wayne Ave				C	0.104		0.516	3100	G	2015
						To US 340 Main St										
5111 Arch Ave	0.08	1500	G	97%	1%	From US 340 Main St				C	0.098		0.629	1600	G	2015
						To US 250 Broad St										
5112 Bridge Ave	0.52	1700	G	99%	0%	From Hopeman Pkwy				C	0.095		0.533	1800	G	2015
						To Sherwood Ave										
5112 Second St	0.74	3700	G	99%	0%	From Sherwood Ave				F	0.095		0.601	3900	G	2015
						To US 340 Delphine Ave										
5113 Charlotte Ave	0.07	980	G	96%	1%	From US 340 Main St				F	0.099		0.508	1000	G	2015
						To US 250 Broad St										
5113 Charlotte Ave	0.65	3300	G	96%	1%	From US 250 Broad St				C	0.099		0.508	3500	G	2015
						To 3rd St										
5113 3rd St	0.18	1100	G	96%	1%	From Charlotte Ave				F	0.105		0.591	1200	G	2015
						To Bath Ave										
5114 Shenandoah Ave	0.58	930	G	97%	1%	From Delphine Ave				C	0.101		0.59	990	G	2015
						To Kirby Ave										
5118 Delphine Ave	1.22	4800	G	88%	1%	From SCL Waynesboro				C	0.101		0.566	5100	G	2015
						To I-64										
5118 Delphine Ave	0.84	9100	G	93%	1%	From I-64				F	0.097		0.555	9700	G	2015
						To Windsor Rd										
5118 Delphine Ave	1.41	8000	G	93%	1%	From Windsor Rd				C	0.097		0.538	8500	G	2015
						To US 250 Main St										
5118 Ramp	0.19	1500	G			From 136-5118 Delphine Ave					0.147		0.593	1500	G	2015
						To I-64 East										
5118 Ramp	0.16	4000	G			From 136-5118 Delphine Ave					0.092			4000	G	2015
						To I-64 West										

Virginia Department of Transportation  
 Traffic Engineering Division  
 2015  
 Annual Average Daily Traffic Volume Estimates By Section of Route  
 City of Waynesboro

Route	Length	AADT	QA	4Tire	Bus	-----Truck-----				QC	K Factor	QK	Dir Factor	AAWDT	QW	Year
						2Axle	3+Axle	1Trail	2Trail							
<b>City of Waynesboro</b>																
(5119) Oak Lane	1.39	530	G	99%	0%	0%	0%	0%	0%	C	0.121		0.712	560	G	2015
(5120) Sherwood Rd	0.18	1000	G	99%	0%	0%	0%	0%	0%	C	0.111		0.661	1100	G	2015
(5121) Guilford Lane	0.07	1200	G	99%	0%	1%	0%	0%	0%	F	0.101		0.531	1300	G	2015
(5121) Guilford Lane	0.08	1700	G	99%	0%	1%	0%	0%	0%	C	0.099		0.526	1800	G	2015
(5122) Lew Dewitt Blvd	1.45	13000	G	99%	0%	1%	0%	0%	0%	C	0.093		0.538	14000	G	2015
Bath Ave		1200	G								0.098		0.608	1200	G	2015
Bath Avenue		320	G								0.125		0.524	320	G	2015
Bookerdale Rd		1600	G	98%	0%	1%	0%	0%	0%	C	0.104		0.551	1600	G	2015
Chatham Rd		210	G								0.156		0.619	220	G	2015
Cherry Ave		330	G								0.139		0.564	350	G	2015
Chestnut Ave		290	G								0.156		0.670	310	G	2015
Duke Rd		100	G	98%	2%	0%	0%	0%	0%	C	0.162			100	G	2015
Edward Avenue		230	G								0.142		0.58	230	G	2015
Florence Ave		1200	G								0.108		0.572	1200	G	2015
Monticello St		100	G								0.191		0.512	110	G	2015
Pelham Drive		3000	G	98%	1%	1%	0%	0%	0%	C	0.093		0.525	3000	G	2015